

TXLP/1

Single Conductor Heating Cable Units for Direct Heating



Applications:

The heating cable units are ideal for direct floor warming and radiant heating in concrete slabs or wood floor constructions. They are also used in snow melting installations, frost protection of roofs, gutters, drains, pipe tacing and soil heating. Each unit has a unique factory made internal splice which is marked = >SPLICE< = on the cable surface.

Construction:

- Solid resistance wire
- XLPE insulation
- Tinned copper earthing conductor
- Aluminum screen
- PVC outer jacket
- Overall diameter: Approx. 6.5 mm (1/4")

Technical data:

- Element values from 300 to 3100 W
- Linear load: 17 W/m
- Series resistance
- Maximum continuously operating temperature outer jacket: 65 °C (149 °F)
- Minimum bending radius: 5 x cable diameter
- Tolerance on conductor resistance: -5 to +10 %
- Highest System Voltage: 600 V



TYPE	LOAD AT 120V (WATT)	CABLE LENGTH (*) (m)	CABLE LENGTH (*) (ft.)	NOMINAL RESISTANCE (ohm/m)
TXLP/1 200/1	200	12.2	40	5.62
TXLP/1 300/1	300	18.3	60	2.50
TXLP/1 400/1	400	24.4	80	1.41
TXLP/1 500/1	500	30.8	101	0.90
TXLP/1 600/1	600	35.4	116	0.68
TXLP/1 730/1	730	43.0	141	0.46
TXLP/1 875/1	875	51.5	169	0.32



TYPE	LOAD AT 240V (WATT)	CABLE LENGTH (*) (m)	CABLE LENGTH (*) (ft.)	NOMINAL RESISTANCE (ohm/m)	OUTER DIAMETER (mm)	WEIGHT PER UNIT (kg)	WEIGHT PER UNIT (lb)	NEXANS Code
TXLP/1 300/17	300	17.7	58	10.0	6.5	1.3	2.9	10022267
TXLP/1 400/17	400	23.5	77	5.62	6.5	1.6	3.5	10022269
TXLP/1 500/17	500	29.3	96	3.6	6.5	1.9	4.2	10022270
TXLP/1 600/17	600	35.1	115	2.5	6.5	2.3	5.0	10022271
TXLP/1 700/17	700	41.2	135	1.84	6.5	2.5	5.5	10022272
TXLP/1 850/17	850	50.0	164	1.24	6.5	3.1	6.8	10022273
TXLP/1 1000/17	1000	58.8	193	0.9	6.5	3.5	7.7	10022261
TXLP/1 1250/17	1250	73.5	241	0.58	6.5	4.2	9.2	10022262
TXLP/1 1400/17	1400	82.3	270	0.46	6.5	4.6	10.1	10022263
TXLP/1 1750/17	1750	103.0	338	0.29	6.5	5.8	12.7	10022264
TXLP/1 2200/17	2200	129.3	424	0.19	6.5	7.2	15.8	10022265
TXLP/1 2600/17	2600	156.1	512	0.13	6.5	8.6	19.0	10022266
TXLP/1 3100/17	3100	185.0	607	0.09	6.5	10.5	23.0	10022268

(*) Plus 2.25 m (7.5 ft) 1 x 1.0 mm² cold lead in each end.

17 Pullman Court, Toronto, ON M1X 1E4

Tel: 416-335-7790 • Fax: 416-335-8071 • Toll Free 877-335-7790 • Fax: Toll Free 877-335-3166 • www.britech.ca • info@britech.ca

Copyright © 2008, Britech Corp.